

ATTACHMENT 11
Group Specifications #940

IFB #23226

State of New York Executive Department
Office of General Services
Procurement Services
 Corning Tower - 38th Floor
 Empire State Plaza
 Albany, NY 12242

GROUP SPECIFICATION

COMMODITY GROUPS: 31555 LIQUID BITUMINOUS MATERIALS	DATE OF ISSUE	10/30/2019
	NO. OF PAGES	4
	SPECIFICATION NO. 940 (Supersedes SPEC-939 dated January 23, 2019)	

BIDDERS ARE REQUESTED TO RETAIN THIS SPECIFICATION FOR FUTURE REFERENCE

Table of Contents

GENERAL INFORMATION 3

MATERIALS:..... 3

SAMPLING, TESTING, INSPECTING, AND REPORTING:..... 3

APPROVED LIST CRITERIA..... 3

REQUIRED QUALIFICATIONS:..... 3

DELIVERY TICKET 4

STORAGE FACILITY:..... 4



GENERAL INFORMATION**MATERIALS:**

Materials offered must be from a NYS Dept. of Transportation approved location.

SAMPLING, TESTING, INSPECTING, AND REPORTING:

All liquid bituminous material intended for use on State agency and non-State agency projects shall be sampled, tested, inspected, certified and shipped in accordance with NYSDOT Materials Method 702-2 Asphalt Emulsion Quality Assurance. The State reserves the right to inspect liquid bituminous material supply facilities and the equipment of any successful bidder at any time for conformance with the requirements listed herein; if deficiencies are found, such deficiencies shall be corrected within 10 days or the contractor will be considered in default.

APPROVED LIST CRITERIA:

The NYSDOT will perform the necessary inspections to establish the approved list of primary sources. Copies of the approved list and written procedures for achieving and maintaining approved list status are available from NYSDOT Materials Bureau, 50 Wolf Road, Pod 3-4, Albany, NY 12232.

REQUIRED QUALIFICATIONS:

A NYS approved liquid asphalt facility must meet the following conditions:

1. The firm's storage facility shall have been approved by the Director, Materials Bureau.
2. The liquid bituminous material shall be obtained from a primary source listed on the NYSDOT approved list of primary sources. An approved primary source is a firm that samples, tests, and certifies that the materials are in conformance with the NYSDOT materials specifications.
3. Asphalt emulsions as defined in NYSDOT Standard Specifications §702, shall be stored in an approved facility having a minimum of one permanent storage tank for each type of asphalt emulsion bid. The tank(s) shall have a storage capacity of at least 10,000 gallons each, be capable of maintaining material homogeneity and have equipment capable of heating the material to the proper application temperature prior to shipment. These tanks shall be equipped with a sampling valve and thermometer. The sampling valve shall be so designed and installed as to be non-clogging and safe.
4. The quantity of liquid bituminous material shall be measured with an accurate truck scale or meter(s) and the quantity shall be ticket printed by machine. The firm shall have evidence available to show that the scale or meter(s) have been tested for accuracy by one of the following three; a competent scale technician recognized by NYSDOT, a representative of NYSDOT, or the County Sealer of Weights and Measures. This accuracy check shall be performed in the current calendar year before any material is supplied. If during the calendar year the accuracy of the measuring device becomes suspect, it shall be recalibrated before any additional material is supplied.
5. The truck scale or meter(s) shall meet the requirements of National Bureau of Standards Handbook 44. The meter(s) shall be equipped with automatic temperature compensation devices to provide quantity in 60° F gallons.

GENERAL INFORMATION (Cont'd)

REQUIRED QUALIFICATIONS: (Cont'd.)

The ticket printer shall meet the following requirements:

- A. Truck Scales: The ticket printer shall machine print in digital form a minimum of two of the following:
 - (1) Tare weight
 - (2) Gross weight
 - (3) Net weight

The scale system shall be interlocked to allow printing only when the scale has come to a complete rest.
- B. Meters: The ticket printer shall machine print in digital form a minimum of two of the following:
 - (1) Beginning meter reading
 - (2) Ending meter reading
 - (3) Total gallons at 60° F
- C. If a meter is used, it shall be permanently installed to connect it with the approved storage tank(s), and shall be used to measure all quantities.

A truck scale shall be located at the storage facility unless the following conditions are met:

- (a) The firm owns the truck scale or has full control of the weighing operations. The scale shall be located in close proximity (approximately 1,000 feet or less) to the storage tanks. The acceptability of the distance will be determined by the NYSDOT.
- (b) The firm provides written proof to the NYSDOT that it has complete access to the truck scale 24 hrs/day, 7 days/week.
- (c) The firm is responsible for calibration and repairs of the weighing equipment.

DELIVERY TICKET:

A delivery ticket shall be provided with each load of bituminous material and filler for joints stating the following:

- 1. Storage facility identification
- 2. Ticket Number
- 3. Date/time
- 4. Item Number and Type
- 5. Quantity ticket printed by machine
- 6. Quantity in 60° F gallons for emulsions.

STORAGE FACILITY:

The bidder shall supply liquid bituminous material in the quantity and date specified on the order. The storage facility shall be approved by NYSDOT before liquid bituminous material can be supplied.

* * * * *